


Product data sheet

TRUSYS® PERFORMANCE WIDE 50 W 4000 K DALI
4058075291034
LEDVANCE



Luminaire inserts with wide light distribution. Product features: Beam angle wide: 90°. Click into place solution with smart click buttons. Luminous efficacy: up to 160 lm/W. Fixed luminare taps. Lumen package 5600 lm, 8000 lm, 11200 lm. Steel-sheet housing. Lens material: PMMA. Type of protection: IP20. Common family design with LEDVANCE. Lifetime (L80/B10): up to 60,000 h. Product benefits: Homogenous light distribution. Easy installation, no tools required for connection. Energy saving and cost-effective. Flexible application due to a range of different lumen packages and beam angles. Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible. Versions with DALI ECG available. Areas of application: Direct replacement for luminaires with fluorescent lamps. Industry halls, high rack warehouse, garages, hardware stores. Discounters, supermarkets. Equipment / Accessories: Mounting rail with fixed integrated 5- and 8-pole cable.

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 5000 W | CRI | 80 |
| Total flux | 8000 lm | LOR | 100% |
| Luminous efficacy | 2 lm/W | ULOR | 2% |
| | | Total power | 5000 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 5,905.51 in
Width: 262.99 in
Height: 155.12 in
Weight: 1660 kg

Adjustability

Fixed

Design

Material impression: Stainless steel
Color of housing: White

Electric

System power: 5000 W
Appliance Class: I

Protection

IP: 20
IK: 04
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...104°F