Product data sheet


PTECDHO L60 60 & PTECD SSR * OP
PROTEC LED HO
DEXTRA



IP 20 CE

Protec LED High Output - Ø174mm, IP20 Recessed High Output Downlighter with a 60 Degree Lens, ABS housing and bezel, zinc plated spring steel fixing clips and anodised semi specular aluminium reflector and opal diffuser. E3 - Emergency control gear (416 lumens output) - Attachments may reduce emergency lumen ouput. ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* Replace * with WH for White or GY for Grey Order the luminaire with trim accessory attachment

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36.9 W	CRI	80
Total flux	3859 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	36.9 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 5.12 in
Diameter: 6.89 in

Adjustability

Fixed

Electric

System power: 36.9 W
Ballast: ECG

Protection

IP: 20
Designation labels: CE