
Product data sheet


PURE3 HEXAGON SURFACE BLACK PRISM. HE
P33A15H-9005C1930L1T OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 20


LED LO 3000K 57,9W 6918lm CRI90 ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 15,2% https://katalog.planlicht.com/en-gb/search?q=pure%203

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	1153 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	34%
		Total power	9.65 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.45 in

Width: 51.50 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 57.9 W

Protection

IP: 20