
# Product data sheet


APEX LINEAL SIMPLE SURFACE 2040MM
AW12-36V9BEXR60
LEDSC4



IP 20


LedsC4 Apex Lineal Simple Surface 2040mm AW12-36V9BEXR60 Lineal lighting system for indoor use. Structure material: Aluminium. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Negre. Warranty: 5 Years. Product net weight (Kg): 0 Product length (mm): 2040 Product width or diameter (mm): 26 Product height (mm): 42 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. LED brand: SAMSUNG. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 38.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. % de Flickering: <1%. Real flux (lm): 3439. Real lm/W: 81. Voltage / frequency range: 220-240/50-60Hz. Voltage: 3. Equipment included: Yes. Total power: 42.2. Power factor: NULL. Dimmable equipment included: CASAMBI.

## Light output 1




1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |




1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |




1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |




1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 7 W | LOR | 100% |
| Lamp flux | 663 lm | Total flux | 663 lm |
| Luminous efficacy | 95 lm/W | Total power | 7 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

### Mounting mode

Ceiling mounted, Standing / Bollard

### Shape and measurements

Length: 1.02 in
Width: 80.31 in
Height: 2.56 in

### Adjustability

Fixed

### Electric

System power: 7 W
Appliance Class: I

### Protection

IP: 20