## Product data sheet

ML56 LED RECESSED DOWNLIGHTS 90 CRI - 5 & 6 INCH ML5609927-594SNB

**COOPER LIGHTING** 








ENERGY STAR® Certified. Learn more at energystar.gov, 600 Design Lumens (typical), 90 CRI, Available in 2700K, 3000K, 3500K and 4000K color temperatures, D2W option - LED warms from 3000K to 1850K, Retrofits existing 5" or 6" housings with screwbase adapter included, Use with Halo 5" & 6" LED new construction & remodel housings, 120V-277V UNV Integral, thermally protected electronic LED driver, Dimmable on 120V phase-control dimmers, Wet location shower listed with reflector and baffle trims, ML56 modules with downlight trims make housings AIR-TITE™ (ASTM E283)

## Light output 1 (integrated)



| Lamp type          | LED     | CCT         | 3000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 9.64 W  | CRI         | 100    |
| Total flux         | 892 lm  | LOR         | 100%   |
| Luminous efficacy  | 93 lm/W | Total power | 9.64 W |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

Adjustability

Fixed

Electric

System power: 9.64 W

Protection

IP: 47