

Product data sheet


LDA3B LED 3 1/2 INCH ADJUSTABLE/SLOPE DOWNLIGHT
LDA3B07R159050D010-E3MRC
COOPER LIGHTING



IP
47

Distributions: 10° - 70°; Optic holds 2 lens media, Lockable 365° rotation and 45° tilt holds any aiming position, Downlight, accent, and pinhole reflectors; 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 250, 700, 1000, 1300, 1800 and 2300, Excellent light control and low aperture brightness, Wavelinx and DLVP connected systems; 5-year warranty, Plaster lathing ring accessory offered for flush reflector transition

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 5000 K |
| Nominal lamp power | 7 W | CRI | 90 |
| Total flux | 754 lm | LOR | 100% |
| Luminous efficacy | 108 lm/W | Total power | 7 W |

Mounting mode

Pole top mounted

Shape and measurements

Height: 0.39 in
Diameter: 3.50 in

Adjustability

Fixed

Electric

System power: 7 W

Protection

IP: 47