

Product data sheet


SPOT REVO MULTIMETRIK 230 TW MEDIUM REVO MULTIMETRIK LED 14.4W RA98 3500K 230V/50HZ IP40 MULTIMETRIK...
386-E0-_-8T-MA-_-WF CLOSED TW@3500K
EXENIA



IP
40

Multimetrik integrates REVO optical technology, offering a regulation system that allows the adjustment of light emission based on specific application needs. The light beam is adjustable from 15° to 60° thanks to the micro-translation of the focal length, ensuring precision and uniformity. The compact design allows integration into Exenia products without altering their aesthetics, ensuring visual continuity with the fixed-beam versions. Interchangeable lenses enable precise and uniform beams, making Multimetrik a versatile solution for various applications. Available in Medium, Compact, and Max variants, with options for dynamic white (2700K-4000K) or fixed temperatures (2700K, 3000K, 3500K, 4000K), with a CRI of up to 98 and color tolerance up to 2 MacAdam Steps.

Light output 1



1 x LED			
Nominal lamp power	16.1 W	LOR	99%
Lamp flux	1237 lm	Total flux	1230 lm
Luminous efficacy	77 lm/W	Total power	16.1 W
CCT	3500 K		
CRI	98		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.40 in
Width: 2.40 in
Height: 4.09 in

Adjustability

Fixed

Electric

System power: 16.1 W

Protection

IP: 40