



Product data sheet

HALO CENTRALIZED SUSPENSION BLACK 760MM
R48Z076-9005C1840L3S
PLANLICHT




LED LO 4000K 24W 1774lm DALI <https://katalog.planlicht.com/en-us/fam-halo/>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	222 lm	LOR	100%
Luminous efficacy	74 lm/W	Total power	3 W

Mounting mode

Pendant

Shape and measurements

Length: 29.92 in

Width: 29.92 in

Height: 2.17 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 20

Designation labels: CE