Product data sheet

INTERMEDIATE ELEMENT 230 BS L3.3 14° 3000K
16.10102.0VXXX
HESS



IP 65

Intermediate Element 230 BS - L3.3 rot. sym. Constructed from aluminium tube section ø 230 mm Module length 300 mm With clear, mineral glass side cover

Light output 1



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	3573 lm	ULOR	100%
Luminous efficacy	132 lm/W	Total flux	3573 lm
CCT	3000 K	Total power	27 W
CRI	70		



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	3534 lm	ULOR	100%
Luminous efficacy	131 lm/W	Total flux	3534 lm
CCT	3000 K	Total power	27 W
CRI	70		



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	3725 lm	ULOR	100%
Luminous efficacy	138 lm/W	Total flux	3725 lm
CCT	3000 K	Total power	27 W
CRI	70		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2882 lm	ULOR	100%
Luminous efficacy	144 lm/W	Total flux	2882 lm
CCT	3000 K	Total power	20 W
CRI	70		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2850 lm	ULOR	100%
Luminous efficacy	142 lm/W	Total flux	2850 lm
CCT	3000 K	Total power	20 W
CRI	70		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	3008 lm	ULOR	100%
Luminous efficacy	150 lm/W	Total flux	3008 lm
CCT	3000 K	Total power	20 W
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 9.06 in
Width: 9.06 in
Height: 12.13 in

Adjustability

Rotatable, Tiltable

Electric

System power: 20-27 W

Protection

IP: 65