


Product data sheet

PRO-STRADA MICRO, 14LEDS OPTIEK 3
41369X2X
PROLUMIA




Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	6.2 W	LOR	100%
Lamp flux	800 lm	Total flux	800 lm
Luminous efficacy	129 lm/W	Total power	6.2 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	6 W	LOR	100%
Lamp flux	800 lm	Total flux	800 lm
Luminous efficacy	133 lm/W	Total power	6 W
CCT	3000 K		
CRI	80		




1 x LED


Nominal lamp power	12.3 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	130 lm/W	Total power	12.3 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	13 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	123 lm/W	Total power	13 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	9.2 W	LOR	100%
Lamp flux	1200 lm	Total flux	1200 lm
Luminous efficacy	130 lm/W	Total power	9.2 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	9.8 W	LOR	100%
Lamp flux	1200 lm	Total flux	1200 lm
Luminous efficacy	122 lm/W	Total power	9.8 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	7.7 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	130 lm/W	Total power	7.7 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	8.1 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	123 lm/W	Total power	8.1 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 16.81 in

Width: 9.02 in

Height: 4.49 in

Electric

System power: 6-13 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC