

# Product data sheet

DEIKO S  
DEIKO-S-ASY17-32LED-3000K-500 MA  
RAGNI




IP  
66

IK  
08

Deiko is composed of a body made of cast aluminium and a silkscreened tempered glass finish, it has an oval shape and a tapered profile giving it a distinctive aesthetic character. Available in two sizes, it can be fixed laterally or on top. The integrated sleeve allows a tilt from 0° to -10° sideways and from -10° to 15° upwards. It features an IK08 tempered glass and the IK10 body with a fully IP66 sealed assembly. The LED module receives up to 80 LED @ 700 mA. Deiko can be equipped with intelligent devices thanks to the integration of a Zagha socket on top.

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 49 W     | LOR         | 100%    |
| Lamp flux          | 6642 lm  | Total flux  | 6642 lm |
| Luminous efficacy  | 136 lm/W | Total power | 49 W    |
| CCT                | 3000 K   |             |         |
| CRI                | 70       |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 27.56 in  
Width: 11.81 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 49 W

## Protection

IP: 66  
IK: 08