Product data sheet

BASIC CATEGORY

B1-A0-00270-01G03-2006050 A270 BASIC (OFFICE1195*180) 54W 5000K PRISM

VARTON



IP 20 IK 02

Budget solution for office luminaires. Stainless steel housing with white powder coating. Application: Administrative facilities. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 198...242 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: УХЛ4 Height/depth, mm: 50 Length, mm: 1 195 Protection class: I Ingress protection (IP): IP20 Impact resistance: IK02 Width, mm: 180 Power factor: 0,95 https://www.varton.ru/products/basic-kategoriya/ofis-basic/a270-basic-ofis-1195-180-analog-2-36/svetodiodnyy-svetilnik-varton-a270-basic-ofisnyy-vstraivaemyy-nakladnoy-54-vt-5000-k-1195kh180kh50-m_1/

Light output 1



1 x LED

Nominal lamp power	54 W	LOR	100%
Lamp flux	6430 lm	Total flux	6429 lm
Luminous efficacy	119 lm/W	Total power	54 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 7.09 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 54 W

Protection

IP: 20
IK: 02