

Product data sheet


WL-R2X055/15ND-P-225M840
0450037
RIDI



IP
20

Diffuser luminaire Design: Single diffuser luminaire. White powder coated steel housing, colour similar to RAL9016. Plastic end caps in luminaire colour white made of UV-stabilized polyamide. Plastic diffuser in UV-stabilised PMMA with internal longitudinal prism structure. Diffuser clips in spring steel. Electronic converter for LED, 230 Volt, 0/50-60 Hz and internal connector block. Suitable for direct voltage operation and use in central battery systems. Mounting: Direct ceiling mounting or semi-recessed mounting using special fixing kit WL-HES. Cable or tube pendant mounting using suitable fixing kits. With wire pendant mounting on ZSPTK, tube pendant and trunking mounting, compensating weights are required (see accessories). WL-R ... P Diffuser P of highly transparent acrylic (PMMA) with satin surface finish and internal linear prisms. Transmittance > 85%, UV-stabilised. Protection rating IP 40. For RIDI-TUBE lamp (order separately), recommended cover: matt

Light output 1



2 x LED			
Nominal lamp power	15 W	LOR	77%
Lamp flux	2060 lm	ULOR	5%
Luminous efficacy	106 lm/W	Total flux	3182 lm
CCT	4000 K	Total power	30 W
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 30 W

Shape and measurements

Length: 24.41 in

Width: 7.01 in

Height: 2.34 in

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: White