Product data sheet


3410 TRIANO DISC LED HIGH-BAY FLOODLIGHT
3410 L100B D DIMD 840 (34100 0017)
SCHUCH



IP 65 IK 09

LED high-bay floodlight, TRIANO disc, 65 W, 10000 lm, 154 lm/W, Class I, IP65, wide beam, 4000 K, CRI≥ 80, Ta -25 °C/+50 °C, L80>100000 h (@Ta 25°C), L80>80000 h (@ Ta max), DALI (DIMD), Optics PC clear, Closure Stainless steel (1.4301), Housing Die-cast aluminium, Colour grey, DB702N, for food areas, for rooms with increased risk of fire. LED high bay luminaire TRIANO disc. Robust die-cast aluminum body with cooling fin structure and integrated ECG housing, powder-coated, built-in control gear, quick-connect plug, eyebolt for 1-point mounting, LED module as well as PC cover with integrated optics. LED module, Multi-Layer technology, with direct connection to the housing for perfect thermal management. Electronic ballast with overload and short-circuit protection, electrical connection via quick connector (FastConnect), male connector pre-installed, female attached. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting)., Width/Diameter 312,00 mm, Height 146,00 mm, Net weight 2,10 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	65 W	CRI	80
Total flux	9999 lm	LOR	100%
Luminous efficacy	154 lm/W	ULOR	7%
		Total power	65 W

Mounting mode

Pendant

Shape and measurements

Height: 5.75 in
Diameter: 12.28 in

Adjustability

Fixed

Electric

System power: 65 W
Appliance Class: I

Protection

IP: 65
IK: 09
Designation labels: CE