

# Product data sheet

DISCOVERY EVO 4K CLO  
57759-402  
FAGERHULT




IP  
44

IK  
10

Installation Four securing holes. For recess or surface mounting on ceilings or walls. Brackets for recessed installation ordered separately, please see accessories. There are holes for a surface mounted installation socket. Connection 230 V integrated LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Cable entry at rear or via knockouts for surface mounting, through wiring 0° or 180°.

Design Luminaire body of polycarbonate and diffuser of opal polycarbonate. Emergency lighting The product is equipped with the ability to connect a monitoring system based on communication via DALI. The system is not dependent on a DALI system being connected or in operation. Dimming e-Sense smartSWITCH – luminaire with PIR sensor for presence detection on/off, IP 20. e-Sense Detect – microwave sensor for on/off function, or absence dimming with the option of switch-off function. e-Sense Move – wireless control between luminaires. Microwave sensor for the on/off function, or absence dimming with the option of switch-off function. Remote control is required for programming. Accessories Anti-ligature casing in white enamelled sheet steel. Supplied with safety screws (tamper-proof torx) IK10, IP 55. Outdoor casing in lacquered aluminium, IK10, IP 55 with the possibility of a surface mounted mains cable.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2652 lm	LOR	100%
Luminous efficacy	140 lm/W	ULOR	3%
		Total power	19 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 14.12 in

Width: 14.12 in

Height: 3.70 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 44

IK: 10