Product data sheet


FLAT SLIM DISC
312638.004.25
RZB



IP 65 IK 02


Series: FLAT SLIM disc Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base: pressure die-cast aluminium, powder-coated. Standard Gore© Protective Vents diaphragm valve to avoid condensation. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Glass fastening: bayonet fixing. Uniform lighting achieved by the use of LED panel boards. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug-and-play connector system. The large connection compartment on the back for convenient connections is also ideal for through wiring. MultiLumen: 2 steps adjustable luminous flux. Factory-set to maximum luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting 3000 K. With daylight sensor, adjustable in multiple steps via DIP switch (2-500 lx). Colour: silver, matt (approx. RAL 9006) Diameter: 380 mm Height: 75 mm Lamp: LED System power: 11 W Rated luminous flux: 1150 lm Luminous efficiency: 105 lm/W System power 2: 11 W Rated luminous flux 2: 1150 lm System power 3: 24 W Rated luminous flux 3: 2450 lm System power 4: 24 W Rated luminous flux 4: 2500 lm Control gear: Regulated power supply Protection class: I Type of protection: IP 65

Light output 1




1 x LED

Nominal lamp power	24 W	LOR	28%
Lamp flux	2500 lm	ULOR	8%
Luminous efficacy	29 lm/W	Total flux	708 lm
CCT	4000 K	Total power	24 W
CRI	80		




1 x LED

Nominal lamp power	24 W	LOR	28%
Lamp flux	2450 lm	ULOR	8%
Luminous efficacy	29 lm/W	Total flux	693 lm
CCT	3000 K	Total power	24 W
CRI	80		



1 x LED

Nominal lamp power	11 W	LOR	28%
Lamp flux	1150 lm	ULOR	8%
Luminous efficacy	30 lm/W	Total flux	325 lm
CCT	3000 K	Total power	11 W
CRI	80		



1 x LED

Nominal lamp power	11 W	LOR	28%
Lamp flux	1150 lm	ULOR	8%
Luminous efficacy	30 lm/W	Total flux	325 lm
CCT	4000 K	Total power	11 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Height: 2.95 in
Diameter: 14.96 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 11-24 W

Protection

IP: 65
IK: 02