
Product data sheet

URBANGLOW LED GEN2 BPS367 LED50-CLO-4S/730 DK T25
BPS367
PHILIPS



Philips UrbanGlow LED gen2 - soft lighting for residential areas UrbanGlow LED gen2 is an elegant street luminaire with a clean design and tight lines. Created by Copenhagen-based Holscher Design, it fits into older urban areas as well as new residential neighborhoods, walkways, and parks. UrbanGlow LED gen2 stands out during the day and after dark thanks to its discreet glow top, which emphasizes the design of the luminaire and provides visual lighting and security. The luminaire also incorporates a Philips round Ledgine to ensure the highest efficiency and the best possible light distribution for all types of roads and paths. UrbanGlow LED gen2 also comes with the option of a satin diffuser that increases visual comfort and reduces glare. The UrbanGlow LED gen2 BPS367 luminaire can be offered with one or two Philips SR (System Ready) sockets to ensure it is future ready. Choose this option and UrbanGlow LED gen2 is ready to pair with stand-alone and advanced control and lighting software applications such as Interact City. The top SR socket is located within the canopy, so it does not alter the beautiful design of the luminaire. In addition, every BPS367 luminaire is uniquely identifiable, thanks to the Signify Service tag app. By simply scanning a QR code, placed inside the door of the mast or directly on the luminaire, you can instantly access the configuration of the luminaire. This makes maintenance and programing operations faster and easier, and enables you to create your digital library of lighting assets and spare parts.

Light output 1



1 x LED

Nominal lamp power	31 W	LOR	82%
Lamp flux	4900 lm	Total flux	4027 lm
Luminous efficacy	130 lm/W	Total power	31 W
CCT	3000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 10.24 in
Diameter: 13.78 in

Electric

System power: 31 W