


Product data sheet

MASK 3 IN-GROUND LUMINAIRES
MK-60269-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear glass lens - Integral control gear - Recessing box in high density polyethylene is included - To ensure efficient drainage, gravel must be used to a depth of 450 mm and width of 300 mm beneath the housing and should also be placed around luminaire - Suitable for drive-over with a maximum load of 4000 kg - Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 10 km/h - Load is transferred by the housing to the foundation

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	433 lm	LOR	100%
Luminous efficacy	29 lm/W	ULOR	100%
		Total power	15 W

Mounting mode

Standing / Bollard, Floor recessed

Shape and measurements

Height: 1.97 in
Diameter: 8.58 in
Weight: 4.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 15 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 08
Surface temperature: 40°C