Product data sheet


REK 533MM 360º EMISSION
55-E030-DL-CL
LEDSC4



IP 66 IK 10

LedsC4 Rek 533mm 360º Emission 55-E030-DL-CL Bollard for outdoor use. Structure material: Aluminium. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 3.33 Product width or diameter (mm): 150 Product height (mm): 534 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: NICHIA. Maximum power of light source: 23.5W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 27.0. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 650. Real lm/W: 24. Voltage / frequency range: 110-277/50-60Hz. Voltage: 11.9. Equipment included: Yes. Total power: 27. Power factor: 0.95. Dimmable equipment included: CASAMBI.

Light output 1



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	650 lm	Total flux	650 lm
Luminous efficacy	24 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.30 in
Width: 6.30 in
Height: 20.91 in

Adjustability

Fixed

Electric

System power: 27 W
Appliance Class: I

Protection

IP: 66
IK: 10