


Product data sheet


NEBULA
F4550009
FLOS



IP
20


Suspension luminaire providing diffused lighting. Central body in die-cast aluminum and 10 blown glass cones of different sizes. Bayonet-type coupling system of the cones for easy cleaning. Die-cast aluminum ceiling attachment with spherical automatic wire clamp. Polycarbonate rose. Steel wire, diameter 2.5 mm. Three-pole FEP-SIL UV-stabilized transparent power cord, length 4000 mm. Net weight 38 kg (may vary because of the blown glass).

Light output 1



4 x Halogen low voltage lamp without reflector			
Nominal lamp power	70 W	Socket	E27
Lamp flux	1240 lm	LOR	84%
Luminous efficacy	15 lm/W	ULOR	45%
CCT	2800 K	Total flux	4180 lm
CRI	99	Total power	280 W

Light output 2



8 x General service incandescent lamp			
Nominal lamp power	70 W	Socket	E27
Lamp flux	1180 lm	LOR	84%
Luminous efficacy	14 lm/W	ULOR	45%
CCT	2821 K	Total flux	7956 lm
CRI	99	Total power	560 W

Mounting mode

Pendant

Electric

System power: 840 W

Shape and measurements

Length: 28.05 in
Width: 27.31 in
Height: 44.58 in

Protection

IP: 20

Adjustability

Fixed