
Product data sheet

6050/606-600-6B2-008850-001
267220
STAHL



Pendant light fitting LED Explosion-protected Type: 6050/606-600-6B2-008850-001 Enclosure material: Aluminium Seawater-resistant Enclosure colour: Standard Protective glass material: Thermally resistant Pressed glass Protective glass version: clear Wire guard: No Version: Pen. light fit. w. wall brac. Lamp wattage: 60 W Lamp: LED Light colour: Neutral white Colour temperature: 5.000 K Colour rendering: ≥ 81 Dimensions (L x W x H): 310 x 298 x 327,5 mm AC rated operational voltage: 120 … 277 V Application range (zones): 1 , 2 , 21 , 22 Gas explosion protection: II 2 G Ex db eb op is IIC T6 Dust explosion protection: II 2 D Ex tb op is IIIC T80 °C Min. ambient temperature: -40 °C Max. ambient temperature: +50 °C Degree of protection (IP): IP66 / IP68 (10 m) Screw connections: 1 x M25 x 1.5 Stopping plug: 1 x M25 x 1,5 For further information, see: r-stahl.com WebCode 6050C

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	60 W	CRI	81
Total flux	7357 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	60 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.96 in
Diameter: 12.20 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 60 W
Voltage: 240 V AC, 120 V AC, 277 V AC, 220 V AC, 230 V AC
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10
Explosion zone suitability: 1

Other operating numbers

Ambient temperature range: -40...122°F