Product data sheet


LADOR 51 SURFACE FACADE LUMINAIRES
LD-30051-VW-30
LIGMAN



IP 65 IK 08


- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry for LD-30011, LD-30001 - Two cable entries for through wiring for LD-30021,LD-30031 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	4.4 W	CRI	-18
Total flux	118 lm	LOR	100%
Luminous efficacy	27 lm/W	ULOR	100%
		Total power	4.4 W

Light output 2 (integrated)




Lamp type	LED	CCT	
Nominal lamp power	3.9 W	CRI	
Total flux	100 lm	LOR	100%
Luminous efficacy	26 lm/W	ULOR	100%
		Total power	3.9 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	80
Total flux	191 lm	LOR	100%
Luminous efficacy	38 lm/W	ULOR	100%
		Total power	5 W

Light output 4 (integrated)



Lamp type	LED	CCT	
Nominal lamp power	4.5 W	CRI	
Total flux	19 lm	LOR	100%
Luminous efficacy	4 lm/W	ULOR	100%
		Total power	4.5 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.23 in
Width: 3.23 in
Height: 3.74 in
Weight: 1.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 17.8 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C