Product data sheet

TRACK SPOTLIGHT MATRIX PRO 32W CRI > 90 3000K ON/OFF WHITE
2000.8979 - MATRIX LED4500-930 40 WH PRO ONF
REGENT



IP 20

Track spotlight Matrix with conductor track adaptor for three circuit track Global Trac Pro, with LED, system power: 32 W, luminous flux of luminaire 4500 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, 1 integral control gear, ON/OFF, control gear box in die-cast aluminium, reflector housing in die-cast aluminium, white, similar to RAL 9016, wide beam, (F), 40°, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0310), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class E and EPREL registration number: 851080 Ø = 127 mm, L = 175 mm, B = 92 mm, A = 210 mm, pivotable 360°, swivelling 45°

Light output 1



1 x LED

Nominal lamp power	32 W	LOR	100%
Lamp flux	4500 lm	Total flux	4515 lm
Luminous efficacy	141 lm/W	Total power	32 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 7.05 in
Width: 12.40 in
Height: 7.99 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 32 W
Appliance Class: I

Protection

IP: 20