


Product data sheet

LATAM - FLOODLIGHT MAX 600W/5700K 78000LM 10DEG
4058075669123
LEDVANCE



LED reflectors (IP66) with high luminous flow for stadiums and sports arenas. Product features: Material: aluminum. High luminous efficacy: up to 130 lm/W. Impact resistance: IK08. Lifetime up to 50,000 h. Type of protection: IP66. Product benefits: Homogeneous luminance distribution and reduced glare. Energy savings of up to 90 % compared to halogen lamp floodlights. Bright, robust and durable. Instant 100 % light, no warm-up time. Low energy consumption. 5 years guarantee. Areas of application: Direct replacement for luminaires using HID lamps. Sports grounds and outdoor facilities. Lighting of large areas. Architectural lighting. Industry. Equipment / Accessories: Equipped with high-power LEDs.

Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	600 W	CRI	70
Total flux	78000 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	600 W

Mounting mode

Wall mounted

Shape and measurements

Length: 18.58 in
Width: 23.27 in
Height: 10.98 in
Weight: 15.8 kg

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 600 W
Appliance Class: I

Protection

IP: 66
IK: 08

Other operating numbers

Ambient temperature range: -22...122°F