# Product data sheet

CIRCULAR OUTWARD 5 RINGS (Ø600 Ø1200 Ø2000 Ø1200 Ø600)
CF4F-00V9AZOU14
LEDSC4



IP 20

LedsC4 Circular Outward 5 Rings (ø600 ø1200 ø2000 ø1200 ø600) CF4F-00V9AZOU14V1 Pendant for indoor use. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2042 Product height (mm): 5500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 330.8W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 25644. Real lm/W: 75. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 340. Power factor: 0.90. Dimmable equipment included: ON-OFF.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 37.4 W | LOR | 100% |
| Lamp flux | 3130 lm | ULOR | 50% |
| Luminous efficacy | 84 lm/W | Total flux | 3130 lm |
| CCT | 2700 K | Total power | 37.4 W |
| CRI | 90 | | |

## Light output 2



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 37.4 W | LOR | 100% |
| Lamp flux | 3130 lm | ULOR | 50% |
| Luminous efficacy | 84 lm/W | Total flux | 3130 lm |
| CCT | 2700 K | Total power | 37.4 W |
| CRI | 90 | | |

### Light output 3



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 69.3 W | LOR | 100% |
| Lamp flux | 5210 lm | ULOR | 49% |
| Luminous efficacy | 75 lm/W | Total flux | 5211 lm |
| CCT | 2700 K | Total power | 69.3 W |
| CRI | 90 | | |

### Light output 4



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 126.6 W | LOR | 100% |
| Lamp flux | 8964 lm | ULOR | 49% |
| Luminous efficacy | 71 lm/W | Total flux | 8965 lm |
| CCT | 2700 K | Total power | 126.6 W |
| CRI | 90 | | |

### Light output 5



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 69.3 W | LOR | 100% |
| Lamp flux | 5210 lm | ULOR | 49% |
| Luminous efficacy | 75 lm/W | Total flux | 5211 lm |
| CCT | 2700 K | Total power | 69.3 W |
| CRI | 90 | | |

### Mounting mode

Pendant, Table luminaire

### Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 1.18 in

### Adjustability

Fixed

### Electric

System power: 340 W

Appliance Class: I

### Protection

IP: 20