## Product data sheet


SPY 39 TRIMLESS IN 93040 24123 9330 DELTA LIGHT





Deltalight

Luminaire, ceiling recessed (indoor use) from Deltalight, named SPY 39 TRIMLESS IN 93040, available in the colour(s): black, brushed alu, brushed anthracite, brushed copper, brushed gold, brushed old bronze, flemish bronze, flemish gold, full white, gold coloured, piano black, white. For recessed mounting, a round opening (for installing a custom mounting kit) is needed and a min. depth for recessing of 130 mm. This luminaire is equipped with LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm with an optional driver, suitable for currents of 350mA to 500mA. Light distributor: reflector 40°.


## Light output 1











1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		











<b>1 x LED</b> Nominal lamp power Lamp flux Luminous efficacy CCT CRI	6 W 787 lm 131 lm/W 3000 K 90	LOR Total flux Total power	73% 573 lm 6 W
<b>1 x LED</b> Nominal lamp power Lamp flux Luminous efficacy CCT CRI	6 W 787 lm 131 lm/W 3000 K 90	LOR Total flux Total power	73% 573 lm 6 W
<b>1 x LED</b> Nominal lamp power Lamp flux Luminous efficacy CCT CRI	9 W 1089 lm 121 lm/W 3000 K 90	LOR Total flux Total power	73% 792 lm 9 W
<b>1 x LED</b> Nominal lamp power Lamp flux Luminous efficacy CCT CRI	6 W 787 lm 131 lm/W 3000 K 90	LOR Total flux Total power	73% 573 lm 6 W
<b>1 x LED</b> Nominal lamp power Lamp flux Luminous efficacy CCT CRI	9 W 1089 lm 121 lm/W 3000 K 90	LOR Total flux Total power	73% 792 lm 9 W

Mounting mode	Electric			
Ceiling recessed	System power: 6-9 W			
Shape and measurements	Appliance Class: II			
Height: 0.04 in	Protection			
Diameter: 1.54 in	IP: 20			

Designation labels: CE