Product data sheet

ARO M

ARO-M-ASY11-48LED-5700K-350 MA


RAGNI



IP 66 IK 09

The ARO luminaire is composed of an aluminum body and a tempered glass finish. With its circular design adorned with raised grooves, it can be configured as a console or pole top luminaire thanks to a flexible sleeve that can be tilted in 5° increments. It can be accompanied by optional accessories such as a dedicated console, equipped with a floodlight located at the rear, offering the possibility of creating a highlighting scenario. With its curved arm, the ARO lyre can also be added to bring harmony to the ensemble. Available in 2 sizes, its the thinnest luminaire in our range. Electrical class I or II, ARO accommodates from 8 to 80 LEDs to provide high performance asymmetric road lighting. An integrated heatsink ensures efficient thermal regulation of the luminaire. Compatible with Zhaga standards and meeting the requirements of smart cities, it is IP66 rated and its shock energy is IK09.

Light output 1



1 x LED

Nominal lamp power	50.7 W	LOR	100%
Lamp flux	7124 lm	Total flux	7124 lm
Luminous efficacy	141 lm/W	Total power	50.7 W
CCT	5700 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Height: 3.94 in

Diameter: 23.62 in

Adjustability

Fixed

Electric

System power: 50.7 W

Appliance Class: I

Protection

IP: 66

IK: 09