# Product data sheet

CIRCULUS PENDANT BLACK 19W LED 3000K RA>80 5046214006

SG ARMATUREN








Pendant suspension on three adjustable wires, wholly uniform light with attractive design, made of powder-coated steel, simple to mount using ceiling electrical box that can be screwed on to all known ceiling outlets/electrical boxes, clips with option of additional looping, current sent from driver to lamp via the adjustable wires so that there are no visible wires, dimmable driver Phase cut-off/DALI, both visible and concealed cabling possible. Light distribution Direct Light technic LED (not exchangeable) 19W 3000K Ra>80 SDCM 3 L80/B10 >50,000 hrs at Ta=25°C L70/B50 >100,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP20 Energy and approvals A+ CE Materials and finish Housing: Steel Colour: Black (RAL 9004) Optics: PMMA Polymethylmethacrylat Mounting/Connection Suspended, Indoor Screwless terminal block

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	1340 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	19 W

## Mounting mode

Pendant

# Shape and measurements

Length: 14.17 in Width: 14.17 in Height: 1.77 in

#### Adjustability

Fixed

#### Design

Color of housing: Black

#### Electric

System power: 19 W Appliance Class: I

# Protection

IP: 20