


Product data sheet

ELSA-2 DL 225 OP 110° 1800 830 PD IR DALI WH
E010299698
ESYLUX



LED downlight, 18 W for ceiling mounting User interface: IR remote control, DALI-Bus Control system: DALI Installation type: Recessed mounting Installation position: Ceiling Dimensions: Height/Depth 60 mm, Ø 240 mm Weight: 1250 g Protection type: IP20 ApplianceClass: Class I Permissible ambient temperature: -20 °C...+40 °C Colour: white, similar to RAL 9003 Nominal voltage: 220 - 240 V AC/DC / 50 - 60 Hz TotalSystemPower: 19 W Luminous flux: 1750 lm Luminous efficacy: 92 lm/W Colour temperature: 3000 K Colour rendering index R_a</sub>: > 80 Rated lifetime L₈₀</sub>B₅₀</sub> at 25 °C: 40000 h<p>ArticleNumber: E010299698</p>https://www.esylux.com/p/E010299698

Light output 1



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	1750 lm	Total flux	1750 lm
Luminous efficacy	92 lm/W	Total power	19 W
CCT	3000 K		
CRI	81		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.24 in
Width: 2.48 in
Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Appliance Class: I

Protection

IP: 20