



# Product data sheet

CYL PRO  
582100.0031.76  
RZB




Series: CYL PRO Wallscaping: elegant and innovative wall luminaire for accent lighting. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Cover made of ceramic-coated toughened glass with bayonet lock. COB LED with socket for easy replacement. Light emission: up and down. Spot lens, narrow beam. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravolock System. Electrical plug and play featuring quick connector. Cable entry granting two cables for loop-through. Driver integrated. Dimmable DALI. MultiLumen: 3 steps adjustable luminous flux. Factory setting is the highest luminous flux. Colour: anthracite metallic (DB703) Length: 100 mm Width: 154 mm Height: 307 mm Lamp: LED System power: 13 W Rated luminous flux: 400 lm Luminous efficiency: 31 lm/W System power 2: 19 W Rated luminous flux 2: 600 lm System power 3: 28 W Rated luminous flux 3: 800 lm Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 65


## Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	800 lm	ULOR	13%
Luminous efficacy	29 lm/W	Total flux	800 lm
CCT	3000 K	Total power	28 W
CRI	80		



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	600 lm	ULOR	13%
Luminous efficacy	32 lm/W	Total flux	600 lm
CCT	3000 K	Total power	19 W
CRI	80		



**1 x LED**

Nominal lamp power	13 W	LOR	100%
Lamp flux	400 lm	ULOR	13%
Luminous efficacy	31 lm/W	Total flux	400 lm
CCT	3000 K	Total power	13 W
CRI	80		

**Mounting mode**

Wall mounted

**Shape and measurements**

Length: 6.06 in

Width: 3.94 in

Height: 12.09 in

**Adjustability**

Fixed

**Electric**

System power: 13-28 W

**Protection**

IP: 65

IK: 07