Product data sheet

LUMINAIRES FOR TRANSPORT INFRASTRUCTURE
V1-S1-7R811-40X32-6616040 TORNADO RU (HIGHWAY) 160W 4000K PLC
VARTON



IP 66 IK 09

AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Protection class: I Nominal voltage: 220...230 Suitable for top end size: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Power factor: 0,95 https://www.varton.ru/products/avtodorozhnoe-osveshchenie/tornado-ru-reestr-rep/tornado-ru-road-dlya-dorogi_1/svetilnik-varton-ulichnyy-tornado-160vt-road-ru-konsolnyy-4000-k-ral7045-seryy-muar/

Light output 1



1 x LED

Nominal lamp power	160 W	LOR	100%
Lamp flux	24000 lm	Total flux	24000 lm
Luminous efficacy	150 lm/W	Total power	160 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 31.89 in
Width: 12.99 in
Height: 4.09 in

Adjustability

Fixed

Electric

System power: 160 W

Protection

IP: 66
IK: 09