


# Product data sheet

LINA45 45-200I-40GEM3/840, B  
45-200I-40GEM3/840  
HALLA




45-200I-40GEM3/840, B Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 2249 x 47 x 59 mm Type of installation: Surface Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

## Light output 1 (integrated, emergency)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 1.5 W    | CRI         | 80     |
| Total flux         | 190 lm   | LOR         | 100%   |
| Luminous efficacy  | 127 lm/W | Total power | 1.5 W  |

## Light output 2 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 30.5 W  | CRI         | 80     |
| Total flux         | 2790 lm | LOR         | 100%   |
| Luminous efficacy  | 91 lm/W | Total power | 30.5 W |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 88.35 in

Width: 1.85 in

Height: 2.32 in

## Adjustability

Fixed

## Electric

System power: 32 W

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

IK: 01