


# Product data sheet

CARLO III (CLEAR ATTACHMENT)  
9.896.5547.02  
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.00 - 4.00 m. - Excellent uniform illumination and glare protection - Unit carrier made of corrosion-resistant cast aluminium, painted - Covers made of aluminium, painted - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - All electrical components are arranged on a block - Easy connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 76 mm, separately

## Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	42 W	LOR	50%
Lamp flux	3200 lm	ULOR	13%
Luminous efficacy	35 lm/W	Total flux	1607 lm
CCT	2899 K	Total power	46 W
CRI	90		

## Mounting mode

Pole top mounted, Ceiling mounted

## Shape and measurements

Height: 20.08 in  
Diameter: 23.62 in

## Adjustability

Height adjustable

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 46 W  
Ballast: ECG

## Protection

IP: 54  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F