Product data sheet


LINA45 145-5B1Z-30GGM3/830, W
145-5B1Z-30GGM3/830
HALLA



IP 20


145-5B1Z-30GGM3/830, W Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1688 x 47 x 69 mm Type of installation: Suspended Distribution: Direct-indirect wide-lighting distribution Optics type: Plastic louvre low UGR Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	250 lm	LOR	100%
Luminous efficacy	167 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	44 W	CRI	80
Total flux	6250 lm	LOR	100%
Luminous efficacy	142 lm/W	Total power	44 W

Mounting mode

Pendant

Shape and measurements

Length: 1.85 in
Width: 66.46 in
Height: 2.72 in

Adjustability

Fixed

Electric

System power: 45.5 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20