



Product data sheet

VEKTER 1 SURFACE WALL LUMINAIRES
VK-30002-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Two cable entries for through wiring on request for VK-30021, 30022, 30041, 30042 - Two cable entries for through wiring as standard for VK-30001, 30002, 30003, 30004 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.8 W	CRI	80
Total flux	3299 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	27.8 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.68 in
Width: 10.24 in
Height: 3.15 in
Weight: 3.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 27.8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C