


Product data sheet

NAOS 2.5FT MPR 6500/840 DALI
95525
TREVOS



modern, low-profile light fitting for indoor lighting in offices, corridors and common rooms; diffuser with multi-layered micropyramid (MPR) optics, with UGR < 19; digitally dimmable DALI driver (AC/DC); Body: steel sheet, white (RAL 9003); Diffuser: multi-layered micropyramid (MPR) optics for distributing light without glare in accordance with EN 12464-1 with UGR < 19; Connection: screwless five-pole terminal block; Power: 37,1 W; Luminaire flux: 5070 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK02; Ambient temperature: -25|35 °C; Weight: 7,6 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	37.1 W	CRI	80
Total flux	6500 lm	LOR	100%
Luminous efficacy	175 lm/W	ULOR	4%
		Total power	37.1 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.48 in

Width: 12.60 in

Height: 1.34 in

Adjustability

Fixed

Design

Color of housing: White

Designer: TREVOS

Electric

System power: 37.1 W

Ballast: ECG

Controller: DALI

Appliance Class: I

Protection

IK: 02

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F