


# Product data sheet

M20/M26H - SPY FOCUS MP 930 MDL  
23332 9300  
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M20/M26H - SPY FOCUS MP 930 MDL, available in the colour(s): black, flemish bronze, flemish gold, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26H - PROFILE, SPLITLINE M20 - PROFILE, SPLITLINE M20 ST - PROFILE. This luminaire is equipped with LED array 17,2W / CRI>90 (R9: 52) / 3000K / 2101lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: MDL = 1-10V or DALI or push button. Light distributor: lens 12-45°.


## Light output 1



1 x LED			
Nominal lamp power	17 W	LOR	73%
Lamp flux	2101 lm	Total flux	1528 lm
Luminous efficacy	124 lm/W	Total power	21 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	17 W	LOR	73%
Lamp flux	2101 lm	Total flux	1528 lm
Luminous efficacy	124 lm/W	Total power	21 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	17 W	LOR	73%
Lamp flux	2101 lm	Total flux	1528 lm
Luminous efficacy	124 lm/W	Total power	21 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling mounted, Contact rail, Wall mounted, Pendant, Wall recessed

### Shape and measurements

Length: 0.79 in

Width: 6.69 in

Height: 0.04 in

### Electric

System power: 21 W

Appliance Class: II

### Protection

IP: 20

Designation labels: CE