


# Product data sheet

ROBERT III (1-ARMED BEADED)  
9.863.5507.06  
LEIPZIGER LEUCHTEN



Mounting height 4,50 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in color - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - scope of supply includes hot galvanized and painted offset pole, dia. 102 mm, and bracket

## Light output 1



### 2 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	80%
Lamp flux	1800 lm	Total flux	2889 lm
Luminous efficacy	52 lm/W	Total power	56 W
CCT	2899 K		
CRI	90		

## Mounting mode

Pole integrated, Ceiling mounted

## Shape and measurements

Height: 11.81 in  
Diameter: 23.62 in

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 56 W  
Ballast: ECG  
Controller: DALI  
Suitable for feed-through wiring

## Protection

Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F