Product data sheet


RACK BOLLARD PORTABLE PLUG&PLAY 260X260X900MM
25-E000-14-XB
LEDSC4



IP 66 IK 06


LedsC4 Rack Bollard Portable Plug&Play 260x260x900mm 25-E000-14-XB Portable for outdoor use. Metres of cable included: 2.5. Structure material: Aluminium. Structure finish: White. Diffuser material: Glass. Diffuser finish: Sandblasted. UV protection. Warranty: 5 Years. Product net weight (Kg): 3.32 Product length (mm): 260 Product width or diameter (mm): 260 Product height (mm): 900 Class 1. IP: IP66. IK: IK06. LED. No. of lampholders or LEDs: 1. LED brand: OSRAM. Maximum power of light source: 13.5W. Colour temperature: SW 2700-3200-4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 26.1. Photobiological risk: RG1. % de Flickering: +/- 3%. Real flux (lm): 760. Nominal flux (lm): 1800. Real lm/W: 51. Voltage / frequency range: 220-240/50-60Hz. Voltage: 9.2. LED brand: OSRAM. Colour temperature: SW 2700-3200-4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 26.1. Photobiological risk: RG1. Real flux (lm): 760. Nominal flux (lm): 1800. Real lm/W: 51. Voltage: 9.2. Equipment included: Yes. Total power: 14.9. Power factor: 0.95. Dimmable equipment included: CASAMBI.

Light output 1




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	726 lm	Total flux	726 lm
Luminous efficacy	46 lm/W	Total power	15.7 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	760 lm	Total flux	760 lm
Luminous efficacy	48 lm/W	Total power	15.7 W
CCT	3200 K		
CRI	80		



1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	656 lm	Total flux	656 lm
Luminous efficacy	42 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	760 lm	Total flux	760 lm
Luminous efficacy	48 lm/W	Total power	15.7 W
CCT	3200 K		
CRI	80		

Mounting mode

Table luminaire, Pendant

Shape and measurements

Length: 10.24 in
Width: 10.24 in
Height: 35.43 in

Adjustability

Fixed

Electric

System power: 15.7 W
Appliance Class: I

Protection

IP: 66
IK: 06