Product data sheet

MIZAR RG 4000K 35W 350MA

SIMON LIGHTING



IP 65

SIMON Mizar Óptica RG 4000K 35W 350mA. Características técnicas: IP66 CRI>70. Acabado Dgclas. 12,75 kg Certificaciones: 2006/95/CE - Directiva Baja Tensión. 2004/108/CE - Directiva CEM. UNE-EN 60598: 2005 Luminarias. UNE-EN 62031: 2009 Módulos LED para alumbrado general. Requisitos de seguridad. UNE-EN 612,7547-2-12,75: 2007 Dispositivos de control de lámpara. UNE-EN 55015:2007 Límites y métodos de medida de las características relativas a la perturbación radioeléctrica de los equipos de iluminación y similares. UNE-EN 61547 Equipos para alumbrado de uso general. Requisitos de inmunidad - CEM. UNE-EN 61000-3-2 Compatibilidad electromagnética (CEM). UNE-EN 61000-3-3 Compatibilidad electromagnética (CEM).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	70
Total flux	5480 lm	LOR	100%
Luminous efficacy	157 lm/W	Total power	35 W

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Height: 6.50 in

Diameter: 19.69 in

Adjustability

Rotatable, Tiltable

Electric

System power: 35 W

Protection

IP: 65