


Product data sheet

91011 LED CG-S
40071352091
EATON EMERGENCY LIGHTING



• Aluminum LED Step light for safety lighting, suitable for recessed mounting • High IP65 protection class • Optimised step illumination achieved through integrated lens optic in the cover • Developed for applications where people are situated in deeper positions for example lecture halls. A special optical arrangement avoids blinding those facing the audience. • Four adjustable levels of brightness (100%, 80%, 60%, 40%) to adapt to the ambient brightness • Side mounting claw-fastening for easy installation in hollow walls or wooden steps (clamping range 3-30 mm) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditure with STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.1 W	CRI	70
Total flux	33 lm	LOR	100%
Luminous efficacy	16 lm/W	Total power	2.1 W

Mounting mode

Wall recessed

Shape and measurements

Length: 10.08 in
Width: 2.80 in
Height: 2.60 in

Adjustability

Free

Design

Color of housing: Anthracite / graphite

Electric

System power: 2.1 W
Ballast: ECG
Suitable for feed-through wiring

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 65