Product data sheet


FENIX 1 - CCT DIP SWITCH 2700K CRI 90 8W CLD BLACK
22068433-39
DISANO



IP 40 IK 07

Housing: in die-cast aluminium with springs for recess mounting. Optics: PMMA Coating: epoxy polyester powder coating resistant to UV rays. Heat Sink: built-in. Wiring: DIP switch setting: the fixture comes with a dip switch driver for the setting of the output current. In this way you, can ensure the best luminous flux for any lighting design. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: galvanised steel wire springs for false ceiling mounting. On request: - DIMM-DALI dimmable version

Light output 1



1 x LED

Nominal lamp power	8 W	LOR	100%
Lamp flux	504 lm	Total flux	504 lm
Luminous efficacy	63 lm/W	Total power	8 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.72 in
Diameter: 4.33 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 8 W
Appliance Class: II

Protection

IP: 40
IK: 07
Designation labels: CE