Product data sheet

SRT-SYSTEM IP20-SRGVOG/1500 LED - GERÄTETRÄGER VARIABEL INDIVIDUAL.LENS.OPTIC | DEVICE MOUNT VARIABLE… 4000 865 DALI2 SG RAL 9006 (SRT+19475006155)


REGIOLUX



IP 20 IK 03

SRT-Quick-fit mounting system, Variable device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour silver grey/white aluminium RAL 9006. Light distribution direct/indirect diffuse distribution by means of Individual.Lens.Optic of PMMA plastic, the single lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The inner rhythm of the 3-row single lens arrangement and the overriding device mount are perfectly in tune to guarantee a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 115° (C0)/110 ° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM LED service life: 50000h L80/B10 (Tq 45°C) Nominal luminous flux: 3953lm Luminaire luminous efficiency: 154lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 26W Energy efficiency class/light source: D Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 45°C) Ambient temperatur: ta -20°C to 45°C Special properties: Ready for IoT UGR lat./long.: max. 24.2 / 23.6 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGVOG /1500 LED 4000 865 DALI2 sg RAL 9006 Article number: 19475006155 Product deep link: https://www.regiolux.de/en/article/19475006155 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	6500 K
Nominal lamp power	25.7 W	CRI	80
Total flux	3953 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	25.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Design

Color of housing: Silver gray

Electric

System power: 25.7 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC