

# Product data sheet

ANDHO MIDI  
931196.002  
RZB




IP  
65

IK  
08

Series: ANDHO midi High-quality surface-mounted downlight for indoor and outdoor use. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass. Rotation-symmetric reflector made of reflex-boosted MIRO-SILVER. Easy installation with a separate ceiling frame and plug connection. 5 pole double terminal for through-wiring. Colour: traffic white, matt (RAL 9016) Diameter: 154 mm Height: 157 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 15 W Rated luminous flux: 2000 lm Beam angle Down: 63° Luminous efficiency: 133 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 65

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 15 W     | CRI         | 80     |
| Total flux         | 2000 lm  | LOR         | 100%   |
| Luminous efficacy  | 133 lm/W | ULOR        | 13%    |
|                    |          | Total power | 15 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 6.18 in  
Diameter: 6.06 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 15 W

## Protection

IP: 65  
IK: 08