
# Product data sheet


SINUS SURFACE WHITE PRISM. 1910MM
R33A191-9016E1830L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 3000K CRI 90 74,6W 8736lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% https://katalog.planlicht.com/en-gb/fam-sinus/

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

## Light output 3 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

### Light output 4 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

### Light output 5 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

### Light output 6 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

### Light output 7 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

## Light output 8 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.32 W | CRI | 90 |
| Total flux | 1092 lm | LOR | 100% |
| Luminous efficacy | 117 lm/W | Total power | 9.32 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 75.20 in
Width: 75.20 in
Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 74.6 W

### Protection

IP: 40