


# Product data sheet

MIRL LAY LED2800-840 M625L LDO KA  
42925621  
ZUMTOBEL



Modular LED recessed luminaire with lens optic. Total power: 19.5 W, Slave luminaire for DALI control (DALI only) with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 85% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 2720 lm, Luminaire efficacy: 139 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Symmetric wide distribution luminaire. Light control via square lens optic for glare-free light distribution with ; low dirt sensitivity and simple cleaning; Luminaire with external electrical connection; Installation as pure lay-in luminaire for modular ceilings with visible grid system; Luminaire wired with halogen-free leads; Dimensions: 1248 x 310 x 38 mm, weight: 4.46 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19.5 W	CRI	80
Total flux	2720 lm	LOR	100%
Luminous efficacy	139 lm/W	Total power	19.5 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 49.13 in

Width: 12.20 in

Height: 1.50 in

Weight: 4.5 kg

## Design

Color of housing: White

## Electric

System power: 19.5 W

Voltage: 220-240 V AC

Controller: DALI

Appliance Class: I

## Protection

IP: 40

Designation labels: CCC, CE, ENEC