## Product data sheet

STORMBELL 80 SUT 1500 NW WFL BK/WH+ ACC. BELL STORMBELL 80 Ø227X89 WH ST18STLOWF940NBW+S8BE227W

LAMP








Downlight to suspend on TRACK 220V rail model STORMBELL 80 SUT 1500 NW WFL BK/WH LAMP brand. Body made of injected aluminum with white/black/Materiality finish, and with black/opal polycarbonate ring, for decorative lighting effect and possibility of accessory color filter, depending on his model. COB LED 4000K color temperature and CRI90. Aluminium reflector WIDE FLOOD. Luminaire with ceiling rose and electronic equipment included. Insulation class I. LED life time: 50000 L90 B10. Compatible with 4 different models of hoods (accessories) that complete the luminaire. + Accessory for suspended luminaries modell ACC. BELL STORMBELL 80 Ø227x89 WH LAMP brand. Body made of aluminum with white/black/Materiality finish.

## Light output 1



1 x LED	
Nominal lamp power	14.7 W
Lamp flux	1225 lm
Luminous efficacy	83 lm/W
CCT	4000 K
CRI	90

LOR	99%
Total flux	1216 lm
Total power	14.7 W

## Mounting mode

Pendant

Shape and measurements

Height: 3.50 in Diameter: 8.94 in

Adjustability

Fixed

Electric

System power: 14.7 W Appliance Class: I

Protection

IP: 20