

Product data sheet

LOUIS I (W. SHIELD ON SIDE FACING BUILDING)
9.615.2036.27
LEIPZIGER LEUCHTEN



IP
55


Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	50%
Lamp flux	3500 lm	ULOR	13%
Luminous efficacy	28 lm/W	Total flux	1735 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	50%
Lamp flux	5600 lm	ULOR	13%
Luminous efficacy	33 lm/W	Total flux	2775 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.23 in
Diameter: 7.87 in

Electric

System power: 62-83 W

Protection

IP: 55