Product data sheet


L409/4328-5101-162-2220-22-850011
278303
STAHL



IP 66 IK 08


Emergency luminaire with LED GRP Type : L409/4328-5101-162-2220-22 -850011 Translucent cover : Clear Translucent cover material : Polycarbonate Enclosure material : Polyester resin Version : Standard Number of lamps : 1 Lamp wattage : 21 W Dimensions (L x W x H) : 857 x 183,5 x 125 mm AC rated operational voltage : 110,00 - 240,00 V Min. ambient temperature : -30 °C Max. ambient temperature : +50 °C Through wiring : With 6 conductors 2.5 mm2 Installed terminal strip : PE + N + L1 + L2 + L3 + L´ Max solid connection terminals: 6,00 mm2 Max. fin. str. conn. terminals: 4,00 mm2 Battery capacity : 7,0 Ah Battery version : NiCd battery, gas-tight Emergency light operation : Continuous light Or stand-by light Operating time : 1.5h emergency lighting oper. LED service life : L90B50 ≥ 100,000 h Battery operating voltage : 6,00 V Self-test function : With (standard) Drilled holes : 3 x M20 Accessories : without Cable glands and entries : can be ordered as an accessory Stopping plugs : Can be ordered as accessories Languages of the documentation: German English Label languages : German English French For further information, see : r-stahl.com WebCode L409A

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	21 W	CRI	82
Total flux	2890 lm	LOR	100%
Luminous efficacy	138 lm/W	ULOR	2%
		Total power	21 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	5000 K
Nominal lamp power	13.65 W	CRI	82
Total flux	1879 lm	LOR	100%
Luminous efficacy	138 lm/W	ULOR	2%
		Total power	13.65 W

Mounting mode

Ceiling mounted, Pendant

Electric

System power: 34.65 W
Appliance Class: I

Shape and measurements

Length: 34.23 in

Width: 6.61 in

Height: 5.07 in

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 66

IK: 08