Product data sheet

HOKAL-HLHX/1200 LED - MIRO® MICRO-PARABOLRASTER SEIDENMATT | SILKY MATT MIRO® MICRO-PARABOLIC LOUV.. 3500 840 ET SG RAL 9006 (60531024165)


REGIOLUX



IP 20 IK 03 CE

Pendant luminaire; Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour silver grey/white aluminium RAL 9006. Light distribution direct distribution by means of Silky matt MIRO® micro-parabolic louvres of aluminium, Reflectivity-enhanced, with low installation height cross blades, self-engaging, continuous effect of louvres with light run installation. 65° < 1500 cd/m²; according to current standard DIN-EN 12464-1. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection via 3-pole connection terminal with plug-in contacts.. Required accessories: order end faces, connectors, through-wiring and Y-wire-rope suspensions SAYE-PS/SAY-DZ with 1900 mm suspension length separately according to luminaire arrangements. Dimensions (LxWxH): 1176mm x 85mm x 72mm Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG0 LED service life: 50000h L80/B10 (Tq 25°C) Nominal luminous flux: 3532lm Luminaire luminous efficiency: 126lm/W Control gear: Electronic driver (1 pcs.) System output: 28W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 Ambient temperatur: ta 25°C UGR lat./long.: 21.0 / 20.3 Certification mark: IP20, Protection class I, 65°<1500 cd/m², F, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: hokal-HLHX/1200 LED 3500 840 ET sg RAL 9006 Article number: 60531024165 Product deep link: https://www.regiolux.de/en/article/60531024165 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	28.1 W	CRI	80
Total flux	3532 lm	LOR	100%
Luminous efficacy	126 lm/W	Total power	28.1 W

Mounting mode

Pendant

Shape and measurements

Length: 46.30 in
Width: 3.35 in
Height: 2.83 in

Design

Color of housing: Silver gray

Electric

System power: 28.1 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE